

Ar
(acid)

a detector to detect signals received from the sensor.

[illegible]

At the time of the deposition, the defendant's Examination Report reached the conclusion that the claims

William M. Lee, Jr.

William M. Lee,

William M. Lee, Jr.
Registration No. 26,935
Lee, Mann, Smith, McWilliams,
Sweeney & Ohlson
P. O. Box 2786
Chicago, IL 60690-2786
312-368-1300
312-368-0034 (Fax)
wlee@intelpro.com (Email)

Version With Markings to Show Changes Made

CLAIMS

5. (Amended) A method according to [any one of claims 2 to 4] claim 2, in which the deposition chamber has an internal pressure of less than 20Pa.
6. (Amended) A method according to [any preceding] claim 1, in which the substrate is the cleaved end of an optical fibre.
8. (Amended) A sensor to claim 7, in which the parylene film is formed by a method according [to any of claims 1 to 6] of forming an interferometer film for an interferometer sensor comprising the step of forming a polymer layer of substantially uniform thickness directly on an interferometer substrate, the layer forming the interferometer film, wherein the polymer layer is deposited by polymerisation of a gas of monomer particles including a para-xylylene.
9. (Amended) Medical analysis equipment having an interferometer sensor assembly comprising:
- an interferometer sensor according to claim 7 [or 8];
 - an interrogation source to provide an interrogation signal to the sensor; and
 - a detector to detect signals received from the sensor.